

DECLARATION OF PERFORMANCE (No.2025/03)					
No. 11					
1. Identification of the product-type		Slate GALLEGAS by CUPA 65			
2. Type of slate		Non carbonated slate originated by tectonic compression			
3. Quarry		San Vicente,Villamartín de Valdeorras, Ourense			
4. Sizes	MIXED	60x45, 60x30,50x45, 50x38,50x30, 50x25,46x30,45x33,45x22,40x38,40x30, 40x25, 40x20, 32x22, 30x20, 27x18, 25x18			
5. Intended uses of the product		Slates for discontinuos roofing an external cladding (UNE-EN 12326-1)			
6. Name and address of the representative		SIG Trading, Adsetts House, 16 Europa View, Sheffield Business Park, Sheffield, S9 1XH. e-mail: gallegas@cupapizarras.com Phone: +34 988 300 006			
7. System of assessment of performance		System 4			

8. Declared performance					
ESSENTIAL CHARACTERISTICS	PERFORMANCE				HARMONISED STANDARD
Deviation from declared length and width	Complies: < ±5mms				EN 12326-1
Deviation from squareness	Complies: <±1%				EN 12326-1
Deviation from straightness of edges	Complies: <±1%				EN 12326-1
Slate type for deviation from flatness	Very Flat	Flat	Normal	Non flat	EN 12326-1
Deviation from flatness		X			EN 12326-1
Slate type for the calculation of the packaged slate thickness	Very smooth	Smooth	Normal	Texturised	EN 12326-1
Nominal thickness and variation	3,7 (±35%) mm 5 (±35%) mm 6,5 (±35%) mm				EN 12326-1
Characteristic modulus of rupture	Transverse	42 MPA	Longitudinal	46 MPA	EN 12326-1
Water absorption	0,06%	Code: W1 (< 0,6%)			EN 12326-1
Freeze thaw test		Fulfill: < 0,6%			EN 12326-1
Thermal cycle test	T1				EN 12326-1
Apparent calcium carbonate content	0,07%	Complies: (< 20%)			EN 12326-1
SO2 exposure test	S1				EN 12326-1
Non carbonate carbon content	0,40%	Complies: (< 2%)			EN 12326-1
External fire exposure / Reaction to fire	Deemed to satisfy, class Broof / Clase A1				EN 12326-1
Dangerous substances emission	None in conditions of use as roofing or external cladding				EN 12326-1
Sustainability	DAPcons®				ISO 14025/ISO21930

* The performance of the product identified in point 1 and 2, is in conformity with the declared performance in table 8

* This declaration is sole responsibility of the manufacturer identified in point 6

Signed on behalf of the manufacturer by the Quality Manager



Sobradelo de Valdeorras, March 24, 2025
Juan López